

2019 Drag Tyre Guide



www.gyracing.com.au

Sept 2019

Drag Tyre Compound Data

Compound	Primary Application Vehicle
D-8	High grip compound for high horsepower radial tire applications
D-2A	High grip compound used for TAD and some bracket applications
D-2G	For Pro Mod and TAFC. High level of grip that can also sustain wheel speed
D-2H	For TF/FC and other high horsepower applications
D-1	For use on dragsters and other lightweight cars
D-4B	For Stock Eliminator and slightly more tractive than D-4A Good
D-4A	for hot or slick track conditions
D-4	Excellent wear/longevity for heavy applications, +3,000 lbs. For use on Stock and Super Stock Radials
D-1A	use on Stock and Super Stock Radials
D-6	Works well on Dragsters and 1,500 - 2,500 lbs. cars
D-5	Works well on Dragsters and 2,000 - 3,200 lbs. cars
D-7	Limited application compound. Designed to eliminate shake
D-3	For heavy manual and automatic cars
HARD	Frontrunners

Listed in order from softest to hardest

Note that in some cases, a softer compound is not necessarily more tractive due to the nature of Goodyear's drag race compounds.



www.gyracing.com.au

Ph: 1800 966 622



Due to currency fluctuations all pricing is available from our website in Au Dollars and includes GST - ex our warehouse

Top Fuel & Funny Car

Material Number	D Number	Compound	Size	Rim Width	Average Diameter	Section Width	Tread Width	Weight Lbs.	Average Circ.	Comments
231233	2747	D-2H	36.0x17.5-16	16	36.6	21.8	17.3	48.0	115.0	BL, LW

Pro Mod, Alcohol, Pro Stock

Material Number	D Number	Compound	Size	Rim Width	Average Diameter	Section Width	Tread Width	Weight Lbs.	Average Circ.	Comments
229258	3122	D-2G	34.5x17.0-16	16	34.8	21.3	17.0	43.0	109.00	
233411	2433	D-4A	33.5x17.0-16	16	33.4	21.5	17.7	43.0	105.00	BL, SS
230874	2912		Shield							

*** Rim width tolerance is plus or minus one inch from specified Rim Width ***

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall

ET - Extended tread life, **MC** - Motorcycle front, **BL** - Bead lock wheel required

ALL DIMENSIONS ARE IMPERIAL



www.gyracing.com.au

Ph: 1800 966 622



Due to currency fluctuations all pricing is available from our website in Au Dollars and includes GST - ex our warehouse

Stock, Super Stock

Material Number	D Number	Compound	Size	Rim Width	Average Diameter	Section Width	Tread Width	Weight Lbs.	Average Circ.	Comments
210598	2790	D-5	28.0x9.0-15	8	28.0	10.7	9.0	21.3	88.0	
210599	2791	D-5	28.0x10.0-15	10	28.0	12.0	10.0	23.1	88.0	
210596	2796	D-5	29.0x11.0-15	10	29.0	12.8	10.9	25.1	91.0	
210597	2797	D-5	29.0x12.0-15	11	29.0	13.9	11.8	25.1	91.0	
219253	4915	D-8	30.0x10.5-15	10	29.6	13.3	10.5	23.5	93.0	R - New for 2019
23623	1909	D-5	30.0x9.0-15	8	30.7	12.4	9.0	25.0	96.5	
190161	2018	D-5	31.0x13.0-15	12	30.6	15.6	12.8	33.4	96.0	MS
219043	4909	D-8	31.0x13.5-15	14	31.7	16.9	13.8	33.0	99.5	R - New for 2019
190162	2019	D-5	31.0x14.0-15	12	31.0	16.2	14.0	35.8	97.0	MS
237741	4917	D-8	31.0x16.0-15	15	31.0	19.4	16.3	37.3	101.0	R - New for 2019
23556	1984	D-5	32.0x14.0-15	14	32.4	17.0	14.4	39.3	101.0	
23540	1672	D-5	32.0x14.5-15	14	32.8	17.7	14.8	39.4	103.0	
190163	2070	D-6	33.0x14.5-15	14	32.8	18.9	14.9	34.1	104.0	
233899	4827	D-1A	30.0x9.0-15	9	29.5	11.8	9.0	22.7	92.5	R, LW
236033	4892	D-1A	30.0x9.0-15	9	29.5	11.8	9.1	21.1	92.5	R, LW
236035	4894	D-1A	30.0x9.0-15	9	30.0	12.0	9.1	21.4	94.0	R, LW

*** Rim width tolerance is plus or minus one inch from specified Rim Width ***

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall

ET - Extended tread life, **MC** - Motorcycle front, **BL** - Bead lock wheel required

ALL DIMENSIONS ARE IMPERIAL



www.gyracing.com.au

Ph: 1800 966 622



Due to currency fluctuations all pricing is available from our website in Au Dollars and includes GST - ex our warehouse

Super Gas

Material Number	D Number	Compound	Size	Rim Width	Average Diameter	Section Width	Tread Width	Weight Lbs.	Average Circ.	Comments
23556	1984	D-5	32.0x14.0-15	14	32.4	17.0	14.4	39.3	101	MS
23540	1672	D-5	32.0x14.5-15	14	32.8	17.7	14.8	39.4	103	MS
23558	1408	D-5	32.0x16.0-15	15	32.4	18.4	16.0	39.6	102	MS
190102	2051	D-4A	32.5x17.0-15	15	32.5	20.8	17.2	41.1	100	
192212	2078	D-5	33.0x15.0-15	14	33.2	17.5	15.0	40.6	104	MS
190167	2052	D-6	33.0x16.0-15	15	32.8	19.6	16.1	38.0	102	
191202	2053	D-4A	33.0x17.0-15	15	32.8	20.6	17.3	42.9	102	SS
233411	2433	D-4A	33.5x17.0-16	16	33.4	21.5	17.7	43.0	105	BL, SS
228522	2211	D-4A	33.5x17.0-16	16	33.4	21.2	17.5	42.5	105	BL, SS
227639	2775	D-2A	33.5x17.0-16	16	33.5	21.1	16.8	40.3	105	BL
235137	2776	D-2A	33.5x17.0-16	16	33.5	21.1	16.8	45.1	105	BL, SS

Top Dragster, Top Sportsman

239367	3111	D-2A	35.0x15.0-16	16	35.0	18.8	14.8	43.5	110	R - New for 2019
235137	2776	D-2A	33.5x17.0-16	16	33.5	21.1	16.8	45.1	105	BL, SS

*** Rim width tolerance is plus or minus one inch from specified Rim Width ***

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall

ET - Extended tread life, **MC** - Motorcycle front, **BL** - Bead lock wheel required

ALL DIMENSIONS ARE IMPERIAL



www.gyracing.com.au

Ph: 1800 966 622



Due to currency fluctuations all pricing is available from our website in Au Dollars and includes GST - ex our warehouse

Motorcycle

Material Number	D Number	Compound	Size	Rim Width	Average Diameter	Section Width	Tread Width	Weight Lbs.	Average Circ.	Comments
103310	2980	D-6	25.0x7.0-18	6	25.4	7.0	6.6	11.3	80.0	BL, LW

Frontrunner

Material Number	D Number	Compound	Size	Rim Width	Average Diameter	Section Width	Tread Width	Weight Lbs.	Average Circ.	Comments
177193	1445	HARD	22.0x2.5-17	2.5	22.0	2.5	1.5	4.5	69.9	ET
215560	2904	HARD	22.0x4.0-17	2.5	22.9	3.4	3.1	5.2	72	
189891	1961	HARD	23.0x5.0-15	4	23.0	6.8	5.0	12.2	72.7	
189955	1962	HARD	24.0x5.0-15	4	24.0	6.8	5.0	11.3	75.8	
215499	2991	HARD	25.0x4.5-15	4	25.0	6.5	4.5	11.6	78.5	LW
190130	1964	HARD	26.0x4.5-15	4	26.0	6.3	4.5	10.8	81.2	
197495	1965	HARD	27.0x4.5-15	4	27.0	7.9	4.5	13.5	84.8	
189822	1966	HARD	28.0x4.5-15	4	28.0	7.7	5.1	12.4	89.1	

*** Rim width tolerance is plus or minus one inch from specified Rim Width ***

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall

ET - Extended tread life, **MC** - Motorcycle front, **BL** - Bead lock wheel required

ALL DIMENSIONS ARE IMPERIAL



www.gyracing.com.au

Ph: 1800 966 622



Due to currency fluctuations all pricing is available from our website in Au Dollars and includes GST - ex our warehouse

Comp Eliminator, Super Comp

Material Number	D Number	Compound	Size	Rim Width	Average Diameter	Section Width	Tread Width	Weight Lbs.	Average Circ.	Comments
206637	2585	D-3	31.0x12.0-15	12	30.8	15.2	12.0	22.6	96.5	
219042	4911	D-8	32.0x14.0-15	14	32.1	17.2	13.8	32.4	101.0	R - New for 2019
193992	1911	D-1	32.0x14.5-15	14	32.2	17.7	15.0	34.1	101	
190102	2051	D-4A	32.5x17.0-15	15	32.5	20.8	17.2	41.1	100	LW, SS
23654	1288	D-7	33.0x12.0-15	12	32.4	16.5	12.3	28.8	102	HG
190163	2070	D-6	33.0x14.5-15	14	32.8	18.9	14.9	34.1	104	
215174	2533	D-2A	33.0x16.0-15	15	32.4	19.9	16.3	39.6	106	
190167	2052	D-6	33.0x16.0-15	15	32.8	19.6	16.1	38.0	102	
215232	2534	D-2A	33.0x17.0-15	15	32.4	20.5	17.4	39.5	104	
227639	2775	D-2A	33.5x17.0-16	16	33.5	21.1	16.8	40.3	105	BL
235137	2776	D-2A	33.5x17.0-16	16	33.5	21.1	16.8	45.1	105	BL, SS

*** Rim width tolerance is plus or minus one inch from specified Rim Width ***
 Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall

ET - Extended tread life, **MC** - Motorcycle front, **BL** - Bead lock wheel required

ALL DIMENSIONS ARE IMPERIAL



www.gyracing.com.au
 Ph: 1800 966 622



Due to currency fluctuations all pricing is available from our website in Au Dollars and includes GST - ex our warehouse

Landspeed

Material Number	D Number	Compound	Size	Rim Width	Average Diameter	Section Width	Tread Width	Weight Lbs.	Average Circ.	Comments
215560	2904	HARD	22.0x4.0-17	2.5	22.9	3.4	3.1	5.2	72	
234517	2952	HARD	21.0x5.0-15	4.5	21.3	5.4	4.1	10.0	68.5	
234515	2953	HARD	23.0x5.0-15	4.5	23.1	7.0	5.0	12.0	74.2	
234514	2954	HARD	25.0x4.5-15	4.5	24.8	6.7	4.0	12.0	79.0	
234516	2956	HARD	28.0x4.5-15	4.5	27.8	7.7	4.5	13.0	88.4	
225063	2934	HARD	28.0x10.0-15	9.5	28.3	13.6	10.0	22.0	89.0	
233188	2870	HARD	30.0x9.0-18	6.5	30.0	8.5	3.0	16.5	93.0	LW

D Number	Min. PSI	Max Load	Max Speed
2904	90 psi	1200 lbs.	300 mph
2952	50 psi	1200 lbs.	300 mph
2953	70 psi	1700 lbs.	300 mph
2954	70 psi	1700 lbs.	300 mph
2956	70 psi	1700 lbs.	300 mph
2934	70 psi	1700 lbs.	300 mph
2870	70 psi	2300 lbs.	320 mph

*** Rim width tolerance is plus or minus one inch from specified Rim Width ***

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall

ET - Extended tread life, **MC** - Motorcycle front, **BL** - Bead lock wheel required

ALL DIMENSIONS ARE IMPERIAL



www.gyracing.com.au

Ph: 1800 966 622

